



solideal
HI-PERFORMANCE TIRES

SOLIDEAL **ECOMATIC**

LOCS *Lower your cost of operation*

SOLID RESILIENT



BEST-IN-CLASS FOR LIGHT DUTY APPLICATIONS



STEEL BEAD REINFORCED HEEL
Prevents rim slip



WIDE AGGRESSIVE TREAD
Increases life and stability



**MATERIAL HANDLING
TIRES & WHEELS**

Complete line of high-performance products from the leading brand
in material handling tires and wheels

camoplastsolideal.com



TIRE SIZE	RIM SIZE ⁽¹⁾	TREAD PATTERN	HEEL		ACTUAL TIRE DIMENSIONS				WEARABLE HEIGHT		LOAD CAPACITY ⁽²⁾ • Counterbalanced lift trucks			
					Overall diameter		Overall width				Load wheel		Steering wheel	
			Normal	Quick	mm	inch	mm	inch	25 km/h • 16 mph		25 km/h • 16 mph			
					kg	lbs	kg	lbs						
5.00-8	3.00D-8	TR	■	■	450	17,7	122	4,8	225	8,9	1415	3100	1090	2400
15x4 1/2-8	3.00D-8	TR	■	■	380	15,0	114	4,5	190	7,5	1040	2300	800	1750
16x6-8	4.33R-8	TR	■	■	406	16,0	146	5,7	203	8,0	1495	3300	1150	2550
18x7-8	4.33R-8	TR	■	■	457	18,0	156	6,1	229	9,0	2145	4750	1650	3650
6.00-9	4.00E-9	TR	■	■	524	20,6	143	5,6	262	10,3	1885	4150	1450	3200
21x8-9	6.00E-9	TR	■	■	526	20,7	185	7,3	263	10,4	2755	6100	2120	4700
6.50-10	5.00F-10	TR	■	■	573	22,6	165	6,5	287	11,3	2340	5150	1800	3950
23x9-10	6.50F-10	TR	■	■	581	22,9	205	8,1	291	11,4	3445	7600	2650	5850
200/50-10	6.50F-10	TR	■	■	453	17,8	191	7,5	227	8,9	2470	5450	1900	4200
7.00-12	5.00S-12	TR	■	■	657	25,9	177	7,0	329	12,9	2920	6450	2240	4950
23x10-12	8.00G-12	TR		■	577	22,7	229	9,0	289	11,4	3770	8300	2900	6400
27x10-12	8.00G-12	TR		■	679	26,7	244	9,6	340	13,4	3900	8600	3000	6600
7.00-15	5.50-15	TR	■	■	731	28,8	185	7,3	366	14,4	3545	7850	2725	6000
8.25-15	6.50-15	TR	■	■	810	31,9	215	8,5	405	15,9	4750	10500	3650	8050
28x9-15	7.00-15	TR	■	■	693	27,3	220	8,7	347	13,6	3770	8300	2900	6400
355/45-15 (28x12.5-15)	9.75-15	TR		■	706	27,8	300	11,8	353	13,9	5525	12200	4250	9400
250-15	7.00-15	TR	■	■	719	28,3	220	8,7	360	14,2	4750	10500	3650	8050
250-15	7.50-15	TR	■		719	28,3	220	8,7	360	14,2	4750	10500	3650	8050
300-15	8.00-15	TR	■	■	815	32,1	257	10,1	408	16,0	5850	12900	4500	9950
355/65-15	9.75-15	TR	■	■	821	32,3	302	11,9	66	2,6	7800	17200	6000	13250
10.00-20	7.50-20	TR	■		1038	40,9	258	10,2	519	20,4	6000	13250	5000	11050
10.00-20	8.00-20	TR	■	■	1038	40,9	258	10,2	519	20,4	6000	13250	5000	11050

© Camoplast Solideal_2012_10_Flyer SD ECOMATIC_EN

ALSO AVAILABLE IN:
GREY NM ➔ *Special non-marking compound with best overall performance and life*

Remarks
⁽¹⁾ Consult tire and wheel manufacturer for confirmation of the suitability of the tire/rim combination particularly with regard to rim profile and wheel strength. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

⁽²⁾ The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. For details please contact the technical department. Loads are valid for intermittent service only, they do not include the additional weight of the tires.